



Technical Data Sheet

CASTROL TECTION GLOBAL 15W-40

APPLICATION:

Castrol Tection Global is a premium 15W-40 mixed fleet diesel engine oil designed to provide excellent protection for fleets containing vehicles from a variety of manufacturers. Its primary application is in European, American and Japanese technology vehicles. Castrol Tection Global 15W-40 is a truly versatile product which can be used in trucks, buses, LCVs, off-road vehicles and equipment and also in agricultural vehicles, and is suitable for use in normally aspirated and turbocharged diesel four stroke engines.

* Not for use in Euro 4 vehicles requiring low SAPS lubricants. For this application we recommend Castrol Enduron Low SAPS.

BENEFITS / FEATURES:

Castrol Tection Global 15W-40 provides excellent protection for a wide variety of engine makes, so is the first choice for on and off-road fleets which contain different vehicle types and require the performance specifications noted below.

- Excellent protection for European, American and Japanese technology engines. Castrol Tection Global 15W-40's versatile formulation provides protection against wear and deposits, ensuring reduced maintenance costs and preventing unscheduled downtime.
- Reduced inventory, Castrol Tection Global 15W-40 is so versatile, mixed fleets need to stock only one engine oil.
- Extended oil drain intervals. Castrol Tection Global 15W-40 is approved by OEMs for use at extended drain intervals, so reducing downtime and servicing costs.

SPECIFICATIONS / PERFORMANCE:

- SAE 15W-40
- ACEA E3, E5, E7
- API CI-4, SL
- MB-Approval 228.3
- MAN M3275
- Volvo VDS-3
- RVI RLD capable
- Caterpillar ECF-2
- Cummins CES 20071, CES 20072, CES 20076, CES 20077, CES 20078
- Mack EO-M Plus

TYPICAL CHARACTERISTICS:

Castrol Tecton Global 15W-40	
Product Code	14322
Density at 15°C	0.89
Viscosity at 40°C mm ² /s	103.6
Viscosity at 100°C mm ² /s	14.2
Viscosity Index	139
Flash Point	224
Pour Point °C	-27
Total Base Number	10.5
CCS at – 20°C	7000

Last Edited: 04/03/2010

This Data sheet and information it contains is considered to be accurate at the date of printing. No warranty or representation, expressed or implied is made as to the accuracy or completeness of the data and information contained in this publication. It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid licence. The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory right of the Buyer of the petroleum product concerned).