



Transmax TQ 95

Automatic Transmission Fluid

Description

Castrol Transmax TQ 95 is specifically developed for use in BTR automotive 4 speed automatic transmissions as used in Ford Falcon and Fairlane cars, Maserati automatic 1995 - 2001 3200GT or Quattroporte models, Ssangyong vehicles with M74LE model BTRA transmissions.

Advantages

- Unique friction characteristics ensure smooth shifts and to prevent squawk during gear changes.
- Enhanced wear control to ensure a long gear set life. It has high shear stability to ensure consistent performance throughout the life of the fluid

Typical Characteristics

Name	Method	Units	Transmax TQ 95
Density @ 15C, Relative	ASTM D4052	g/ml	0.870
Colour	ASTM D1500	-	Red
Appearance	Visual	-	Bright and Clear
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	7.2
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	38
Viscosity Index	ASTM D2270	None	Report
Pour Point	ASTM D97	°C	-42
Viscosity, Brookfield @ -40C	ASTM D2983	mPa.s (cP)	35000
Flash Point, COC	ASTM D92	°C	216

Product Performance Claims

BTRA - 5M-44
BTRA - 5M-52

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Transmax TQ 95

26 Sep 2011

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

10 Junction Avenue , Parktown , Johannesburg , 2193, South Africa
+27 11 488 5111, 0860 222 166 (SA), 0800 111 551 (SA)
www.castrol.co.za