



Castrol EDGE Professional TWS 10W-60

Castrol EDGE - Strength To Perform

Description

Castrol EDGE Professional with *Fluid Strength Technology™* is Castrol's strongest and most advanced range of engine oils, it is an SAE 10W-60, and its unique adaptive strength reduces metal to metal contact across a range of different driving speeds. Castrol EDGE Professional - lowers friction, maximises engine performance.

Castrol EDGE Professional TWS 10W-60 gives you the confidence to demand maximum engine performance from M Series vehicles, competition and the latest technology high powered engines which operate under higher pressures requiring an oil with unsurpassed strength and performance credentials.

Castrol EDGE Professional TWS 10W-60 is proven in tests to deliver outstanding oil strength. Micro-filtered and with its signature fluorescent colour it is your guarantee of Professional quality.

Castrol EDGE Professional. Strength to Perform - Freedom to Drive.

Application

Castrol EDGE Professional TWS 10W-60 is suitable for use in automotive petrol and diesel engines where the manufacturer recommends an ACEA A3/B3, A3/B4, API SN/CF or earlier specification 10W-60 lubricant.

Castrol EDGE Professional TWS 10W-60 is endorsed for use in BMW M - Models.

Advantages

Castrol EDGE Professional TWS 10W-60:

- Delivers and sustains maximum horsepower for longer, even when under pressure.
- Protects short and long term engine performance.
- Ensures maximum protection under all driving conditions, speeds and temperatures.
- Reduces engine deposits to help maximise engine response.
- Recommended by BMW for M - Models.

Typical Characteristics

Name	Method	Units	Castrol EDGE Professional TWS 10W-60
Product code			11231
Density @ 15C, Relative	ASTM D4052	g/ml	0.853
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	22.7
Viscosity, CCS -25C (10W)	ASTM D5293	mPa.s (cP)	4879
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	160
Viscosity Index	ASTM D2270	None	173
Pour Point	ASTM D97	°C	-39
Flash Point, PMCC	ASTM D93	°C	203
Ash, Sulphated	ASTM D874	% wt	1.29

Product Performance Claims

ACEA A3/B3, A3/B4

API SN/CF

VW 501 01 / 505 00

Exclusive Approval For BMW M-Models

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol EDGE Professional TWS 10W-60

18 Jan 2012

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

10 Junction Avenue , Parktown , Johannesburg , 2193, South Africa
+27 11 488 5111, 0860 222 166 (SA), 0800 111 551 (SA)

www.castrol.co.za

Page 2 of 2